




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : H04J 14/02	A1	(11) International Publication Number: WO 95/05041 (43) International Publication Date: 16 February 1995 (16.02.95)
(21) International Application Number: PCT/GB94/01713 (22) International Filing Date: 4 August 1994 (04.08.94) (30) Priority Data: 93306146.7 4 August 1993 (04.08.93) EP (34) Countries for which the regional or international application was filed: GB et al. (60) Parent Application or Grant (63) Related by Continuation US 08/191,501 (CIP) Filed on 4 February 1994 (04.02.94) (71) Applicant (for all designated States except US): BRITISH TELECOMMUNICATIONS PUBLIC LIMITED COMPANY [GB/GB]; 81 Newgate Street, London EC1A 7AJ (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): STALLEY, Kevin, Derek [GB/GB]; The Well House, Shottisham, Woodbridge, Suffolk IP12 3RT (GB). CLARKE, Donald, Eric, Arthur [GB/GB]; 65 Northgate Street, Colchester, Essex CO1 1EY		(GB). ROSHER, Paul, Adrian [GB/GB]; 18 Stewart Young Grove, Kesgrave, Ipswich, Suffolk IP5 7YH (GB). (74) Agent: PRATT, David, Martin; BT Group Legal Services, Intellectual Property Dept., 13th floor, 151 Gower Street, London WC1E 6BA (GB). (81) Designated States: AU, CA, CN, JP, KR, NZ, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.

(54) Title: OPTICAL FIBRE COMMUNICATIONS SYSTEM



(57) Abstract

An optical fibre communications system comprises a head end connected to n customers by an optical fibre network. The head end comprises a transmitter unit (1, 5) and a receiver unit (2), and each of the customers has an optical network unit (9) comprising an optical receiver (10) and a transmitter unit (11). The head end transmitter and receiver units (1 and 2) are connected respectively to the receivers (10) and the transmitter units (11) of the customer optical network units (9) by at least one passive optical network (3, 4 or 3'). The head end transmitter unit is constituted by an optical transmitter (1) driven by a sub-carrier multiplexer (5), the sub-carrier multiplexer having a plurality of input sub-carriers at different frequencies. One of the sub-carriers carries interactive signals provided by a further transmitter unit (6). The remaining sub-carriers carry broadband service signals. Each customer transmitter unit (11) includes an optical transmitter and means for multiplexing interactive signals and control signals to drive said optical transmitter. The head end includes a system control unit (8) for controlling the transmission of broadband services by the head end transmitter unit (1, 5) in dependence upon the control signals received by the head end receiver unit (2) from the customer transmitter units (11).

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Larvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

OPTICAL FIBRE COMMUNICATIONS SYSTEM

This invention relates to an optical fibre communications system, and in particular to an optical fibre communications system capable of carrying both broadband signals and interactive signals such as telephony and ISDN.

In optical transmission systems, the radiation used is not necessarily in the visible region of the electromagnetic spectrum, and so the words "optical" and "light" when used in this specification are not to be interpreted as implying any limitation to the visible spectrum. For example, the wavelengths preferred for transmission through silica optical fibres are in the infra red region of the spectrum, because the low loss minima of silica fibres occur at about 1.3 and 1.5 microns.

Optical transmission systems may be utilised to distribute both interactive services such as telephony and ISDN, and broadband services such as video channels, video telephony and information services such as picture videotext. In general, the primary service, at least as presently measured in terms of subscriber lines, is telephony. Increasingly, however, there is a perceived need for optical transmission systems to be able to carry both interactive services and broadband services.

Various techniques are available for separating different services for transmission over the same lines, for example the transmitted signals may be time, wavelength or sub-carrier frequency multiplexed. Wavelength division multiplexing, with different services on different wavelengths, would require additional optical transmitters and receivers to be installed wherever an expansion of services and additional channels is required.

Conventional broadband service provision, for example that provided by the cable TV companies, uses amplitude modulated (AM) transmission. Unfortunately, AM transmission is not suitable for passive optical networks (PONs), due to signal-to-noise-ratio limitations and intermodulation

- 2 -

distortion imposed by optical transmitters. Although lasers are being developed which offer the prospect of meeting the required performance in these two areas, the optical budget achievable will still be very limited, and optical splitting
5 of the signal will, therefore, be minimal.

The present invention provides an optical fibre communications system comprising a head end connected to n customers by an optical fibre network, the head end comprising a transmitter unit and a receiver unit, and each
10 of the customers has an optical network unit comprising an optical receiver and a transmitter unit, the head end transmitter and receiver units being connected respectively to the receivers and the transmitter units of the customer optical network units by at least one passive optical
15 network, said at least one passive optical network constituting the optical fibre network, wherein the head end transmitter unit is constituted by an optical transmitter driven by a sub-carrier multiplexer, the sub-carrier multiplexer having a plurality of input sub-carriers at
20 different frequencies, one of said sub-carriers carrying interactive signals provided by a further transmitter unit, and the remaining sub-carriers carrying broadband service signals, wherein each customer transmitter unit includes an optical transmitter and means for multiplexing interactive
25 signals and control signals to drive said optical transmitter, and wherein the head end includes a system control unit for controlling the transmission of broadband services by the head end transmitter unit in dependence upon the control signals received by the head end receiver unit
30 from the customer transmitter units.

Advantageously, the head end optical transmitter is arranged to operate at a first predetermined wavelength, and each of the customer optical transmitters is arranged to operate at a second predetermined wavelength. Preferably,
35 the first predetermined wavelength lies in the range of from 1500nm to 1650nm, and the second predetermined wavelength lies in the range from 1260nm to 1360nm.

In a preferred embodiment, said at least one passive optical network is constituted by separate first and second simplex passive optical networks, each having an n-way split, the first simplex passive optical network connecting the head end transmitter unit to the receivers of the customer optical network units, and the second simplex passive optical network connecting the head end receiver unit to the transmitter units of the customer optical network units. Alternatively, said at least one passive optical network may be constituted by a duplex passive optical network having an n-way split. In this case, the head end transmitter unit and the head end receiver unit are connected to the duplex passive optical network via a wavelength division multiplexer (WDM), and the receiver and transmitter unit of each customer are connected to the duplex passive optical network via a respective WDM.

Preferably, the system further comprises a video server for supplying video film signal information to the sub-carriers carrying broadband service signals. In this case, the system may further comprise a switch for controlling the supply of video film signal information from the video server to the sub-carriers carrying broadband service signals. Advantageously, the system further comprises a broadcast distribution network for supplying broadcast television channels to the sub-carriers carrying broadband service signals via said switch. Preferably, the broadcast distribution network and the video server are connected to the switch by an SDH ring.

Conveniently, a respective receiver/tuner unit is associated with the receiver of each of the customer optical network units, the receiver/tuner units being arranged to convert received video film signal information into a form suitable for reception by a television apparatus.

Advantageously, the interactive signals are digitally phase modulated onto said one sub-carrier. Preferably, the broadband service signals are frequency modulated onto said remaining sub-carriers. Alternatively, the broadband service signals are digitally phase modulated onto said remaining

sub-carriers. In either case, quadrature phase shift keying (QPSK) may be used for digitally phase modulating signals onto said sub-carrier(s).

Two forms of optical fibre communications system, each of which is constructed in accordance with the invention, will now be described, by way of example, with reference to the accompanying drawings, in which: -

Figure 1 is a schematic representation of the first system;

Figure 2 is a schematic representation of the second system; and

Figure 3 is a schematic representation of the head end of a modified form of either of the systems of Figures 1 and 2.

Referring to the drawings, Figure 1 shows a TPON/BPON optical fibre communications system having a head end station including a BPON transmitter 1 and a TPON receiver 2. The transmitter 1 is connected to 256 customer premises (only one of which is shown) via a simplex PON indicated generally by the reference numeral 3. Similarly, the TPON receiver 2 is connected to the 256 customer premises by a simplex PON indicated generally by the reference numeral 4. The BPON transmitter 1 is basically a laser provided with control/monitoring circuitry. If necessary, an optical amplifier (such as a fibre amplifier) will be provided downstream of this laser. A suitable BPON transmitter is that described in the article "Broadband systems on passive optical networks" (British Telecom Technology Journal, vol 7, no. 2, pages 115-122, April 1989). The TPON receiver 2 is a standard TPON optical receiver, for example of the type described in the article "The provision of telephony over passive optical networks" (British Telecom Technology Journal, vol 7, no. 2, pages 100-114, April 1989).

The BPON transmitter 1 is driven by an FM sub-carrier multiplexer 5 which has 32 input sub-carriers each of up to 40Mbit/s capacity. This technique of sub-carrier multiplexing enables transmission of a multiplex of the 32

- 5 -

sub-carriers on an optical wavelength, here chosen to be 1550nm. The sub-carriers have frequencies ranging from 950MHz up to 2GHz, with the carriers being separated by 27MHz. Each of 31 of the carriers can be either frequency modulated or digitally phase modulated. When frequency modulated, only a single analogue video channel is conveyed on each of the 31 carriers. Each carrier can also be digitally phase modulated using QPSK of up to a bit rate of 40Mbit/s, and so, as each video channel can be compressed to about 2Mbit/s, each of the 31 carriers can support between 16 and 18 compressed video channels whereby the complete multiplex can support 558 channels. The remaining sub-carrier carries signals from a TPON head end 6 which provides interactive services such as telephony, ISDN, fax etc. The TPON head end 6 may be a TPON Bit Transport System (BTS) of the type described in the above-mentioned article "The provision of telephony over passive optical network".

The TPON head end 6 is connected to the main telephony network as indicated by the arrow 7. The entire head end constituted by the BPON transmitter 1, the TPON receiver 2, the sub-carrier multiplexer 5 and the TPON head end 6 are controlled by a control/network management system indicated generally by the reference numeral 8.

Each of the customer premises includes an optical network unit (ONU) 9 which comprises a BPON receiver 10 and a TPON sub-system unit 11. The video channel information output by the receiver 10 is fed to a television 12 via a control box 13 (similar to the set-top receiver used to tune satellite TV signals). The BPON receiver 10 is an avalanche photodiode (APD) of the type described in the above-mentioned article "Broadband systems on passive optical networks". The TPON sub-system unit 11 is a standard BTS network termination unit of the type described in the above-mentioned article "The provision of telephony over passive optical networks". This unit 11 includes an optical transmitter (such as a Fabry-Perot laser) for transmitting video request signals, telephony and other interactive service signals at a

- 6 -

wavelength of 1300nm using a time division multiple access (TDMA) transmission technique. The unit 11 also includes an optical receiver and an RF amplifier circuit for driving the control box 13.

5 The TPON sub-system unit 11 includes a demodulator 14 for providing downstream TDM TPON signals to the TPON sub-system unit 11. The TDM signals are then demultiplexed to drive customer premises equipment (CPE) such as a telephone 15. Outgoing (upstream) telephony from the telephone 15 is
10 multiplexed by the TPON sub-system unit 11 for TDMA transmission via the PON 4 to the TPON receiver 2 at the head end. Upstream video request signalling from the customer is passed from the control box 13 to the TPON sub-system unit 11, and then back to the head end via the PON 4 and the TPON
15 receiver 2. The control box 13 can be controlled via an infra red remote control unit 16.

 The BTS of the TPON head end 6 receives speech and data channels which arrive on the line 7 as part of a 2 Mbit/s PCM stream with signalling. Within the TPON head end
20 6, the statistically-multiplexed signalling for 30 64 kbit/s speech and data channels is converted to a form which can be delivered to individual ONUs 9. The signalling for each speech and data channel, formatted into 8 kbit/s channels, is used, for example, to control ringing and to provide loop
25 disconnect detection. Each 64 kbit/s speech and data channel, and its associated 8 kbit/s signalling channel, is then multiplexed with the other 29 channels to form a 2.16 Mbit/s ($=30 \times (64+8)$ kbit/s) signal which, together with some spare bits, forms a 2.352 Mbit/s interface to the TPON head
30 end 6. The combination of speech and data signals and the associated signalling is referred to as traffic data. The function of the TPON head end 6 is to transport this traffic data transparently to the ONUs 9 and vice-versa. Within the TPON head end 6, the 2.352 Mbit/s stream is bit interleaved
35 with similar streams derived from seven other PCM streams, giving a total bit rate of 18.816 Mbit/s which, when control overheads are added, becomes 20.48 Mbit/s on the PON 3.

- 7 -

The PON 3 intrinsically ensures that all of the 20.48 Mbit/s stream is received at all of the ONUs 9. Each particular ONU 9 can be instructed by the TPON head end 6 to select its traffic, starting anywhere in the multiplex, and to extract a given number of 8 kbit/s channels that were contiguous in the original 2.352 Mbit/s streams. In the case of a speech channel, an ONU 9 selects nine 8 kbit/s channels, 64 kbit/s for speech and 8 kbit/s for the associated signalling. The ONU 9 then converts these to a form for connection to the telephone 15.

In the reverse direction, a reciprocal process occurs; the (64+8) kbit/s traffic data derived from the telephone 15 plus control signals are transmitted onto the PON 4 by bit interleaving with other ONUs 9. The bits are actually interleaved by the PON 4 and, at the TPON head end 6, they appear as a continuous and perfectly interleaved stream. The ranging mechanism which ensures that this happens is controlled by the TPON head end 6 using the control signals in the 20.48 Mbit/s multiplex. The BTS is described in greater detail our European patent specifications 318331, 318332, 318333, 318335, 502004 and 512008.

In use, the head end broadcasts all the information on all 32 sub-carriers to all of the associated 256 customers via the PON 3. As mentioned above, 31 of the sub-carriers carry video channels, telephony and other interactive services being provided on the remaining sub-carrier dedicated for such services.

The video channels carried by the remaining 31 sub-carriers are provided by a video server 17. The arrangement is such that the network can transmit up to 560 video channels simultaneously (assuming each video channel is compressed to 2Mbit/s, and each sub-carrier carries 18 video channels). If a given subscriber wants to view a particular video film, the necessary request is sent to the head end by that customer's control box 13 (possibly using the remote control unit 16), the associated TPON sub-system unit 11 and the PON 4. The signalling information is received by the

- 8 -

TPON receiver 2, and is passed on to the video server 17 via the TPON head end 6 and the control system 8. The video server 17 then transmits the requested video film on to a spare video channel for transmission to that customer together with a control signal which enables that customer's control box 13 to receive that video channel.

Figure 2 shows a modified form of the system shown in Figure 1, in which the two simplex PONs 3 and 4 are replaced by a duplex PON 3'. Accordingly, like reference numerals will be used for like parts, and only the modifications will be described in detail. In this embodiment, all the downstream signalling takes place in exactly the same manner as for the embodiment of Figure 1, that is to say the head end broadcasts all the information on all 32 sub-carriers to all of the associated 256 customers via the BPON transmitter 1 and the PON 3'. Upstream signalling is, however, also carried on the PON 3', with the TPON sub-system unit 11 of each customer being connected to its associated fibre via a WDM 18. Similarly, the TPON receiver 2 is connected to the PON 3' via a WDM 19 upstream of the first splitting point. As before, downstream signalling is at 1550nm, and upstream signalling at 1300nm.

Figure 3 shows a modified form of head end for use with either of the systems of Figures 1 and 2. In the modified head end, a switch 18 is positioned between the video server (or video distribution network) 17 and the FM sub-carrier multiplexer 5. A broadcast distribution network 19 is also connected to the switch 18, this network providing up to several hundreds of compressed digital video channels or broadcast television programmes. The modified head end can, therefore, provide customers with broadcast television channels as well as requested video films. The video distribution network 17 and the broadcast distribution network 19 need not be provided in the head end itself, and are preferably connected to the head end via a synchronous digital hierarchy (SDH) or SONET ring.

It will be apparent that the systems described above

have a number of advantages compared with known broadband transmission systems. In particular, the use of FM sub-carrier multiplexing has the following advantages, namely: -

1. optical constraints which are similar to those for digital (baseband) modulation;
2. low cost lasers can be used, as linearity requirements are less stringent;
3. a high PON split is possible without optical amplification;
4. the frequency band is compatible with the satellite TV receiver band of 950MHz to 2000MHz;
5. the equipment used is compatible with terrestrial radio systems;
6. very small, low power optical receivers can be used;
7. as the BPON transmitter 1 is used to transmit the downstream TPON signals, a separate optical TPON transmitter at the head end is not required, and a separate optical receiver at the ONU is not required, thereby considerably reducing the cost of the optics.

The compatibility with low-cost satellite receivers already in use is particularly important. Thus, the customer ONU 9 could directly replace a satellite dish, in which case it would be connected directly to the set-top receiver (control box 12), and could be powered by that receiver from the supply intended for the low noise block (LNB).

Each of the systems described above is, therefore, capable of delivering advanced interactive broadband services, such as video on demand direct to the home on fibre. The FM-BPON approach described is capable of a high level optical split, and the integration of the TPON technology with this approach provides a powerful interactive capability.

It will be apparent that the system described above could be used to carry other broadband services than video on demand. For example, each of the TPON/BPON systems described could be modified to provide broadcast TV, satellite TV from

- 10 -

a central dish, and innovative new dial-up services applications such as telepresence, broadband videoconferencing, virtual reality and video games.

CLAIMS

1. An optical fibre communications system comprising a head end connected to n customers by an optical fibre network, the head end comprising a transmitter unit and a receiver unit, and each of the customers has an optical network unit comprising an optical receiver and a transmitter unit, the head end transmitter and receiver units being connected respectively to the receivers and the transmitter units of the customer optical network units by at least one passive optical network, said at least one passive optical network constituting the optical fibre network, wherein the head end transmitter unit is constituted by an optical transmitter driven by a sub-carrier multiplexer, the sub-carrier multiplexer having a plurality of input sub-carriers at different frequencies, one of said sub-carriers carrying interactive signals provided by a further transmitter unit, and the remaining sub-carriers carrying broadband service signals, wherein each customer transmitter unit includes an optical transmitter and means for multiplexing interactive signals and control signals to drive said optical transmitter, and wherein the head end includes a system control unit for controlling the transmission of broadband services by the head end transmitter unit in dependence upon the control signals received by the head end receiver unit from the customer transmitter units.

2. A system as claimed in claim 1, wherein the head end optical transmitter is arranged to operate at a first predetermined wavelength, and each of the customer optical transmitters is arranged to operate at a second predetermined wavelength.

3. A system as claimed in claim 2, wherein the first predetermined wavelength lies in the range of from 1500nm to 1650nm, and the second predetermined wavelength lies in the range from 1260nm to 1360nm.

- 12 -

4. A system as claimed in any one of claims 1 to 3, wherein said at least one passive optical network is constituted by separate first and second simplex passive optical networks, each having an n-way split, the first
5 simplex passive optical network connecting the head end transmitter unit to the receivers of the customer optical network units, and the second simplex passive optical network connecting the head end receiver unit to the transmitter units of the customer optical network units.
- 10 5. A system as claimed in any one of claims 1 to 3, wherein said at least one passive optical network is constituted by a duplex passive optical network having an n-way split.
- 15 6. A system as claimed in claim 5 when appendant to claim 2, wherein the head end transmitter unit and the head end receiver unit are connected to the duplex passive optical network via a WDM, and the receiver and transmitter unit of
20 each customer are connected to the duplex passive optical network via a respective WDM.
7. A system as claimed in any one of claims 1 to 6, further comprising a video server for supplying video film
25 signal information to the sub-carriers carrying broadband service signals.
8. A system as claimed in claim 7, further comprising a switch for controlling the supply of video film signal
30 information from the video server to the sub-carriers carrying broadband service signals.
9. A system as claimed in claim 8, further comprising a broadcast distribution network for supplying broadcast
35 television channels to the sub-carriers carrying broadband service signals via said switch.

- 13 -

10. A system as claimed in claim 9, wherein the broadcast distribution network and the video server are connected to the switch by an SDH ring.

5 11. A system as claimed in any one of claims 7 to 10, wherein a respective receiver/tuner unit is associated with the receiver of each of the customer optical network units, the receiver/tuner units being arranged to convert received video film signal information into a form suitable for
10 reception by a television apparatus.

12. A system as claimed in any one of claims 1 to 11, wherein the interactive signals are digitally phase modulated onto said one sub-carrier.

15

13. A system as claimed in any one of claims 1 to 12, wherein the broadband service signals are frequency modulated onto said remaining sub-carriers.

20 14. A system as claimed in any one of claims 1 to 12, wherein the broadband service signals are digitally phase modulated onto said remaining sub-carriers.

15. A system as claimed in claim 12 or claim 14, wherein
25 QPSK is used for digitally phase modulating signals onto said sub-carrier(s).




Fig.1.




Fig.2.

3/3




Fig.3.

SUBSTITUTE SHEET (RULE 26)

INTERNATIONAL SEARCH REPORT

International application No.
PCT/GB 94/01713A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04J14/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 H04J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP,A,0 380 945 (STANDARD ELEKTRIK LORENZ) 8 August 1990 see column 2, line 21 - column 3, line 32 see column 5, line 20 - column 6, line 3 see column 6, line 38 - column 7, line 4 ---	1-7, 12-15
X	EP,A,0 386 466 (STANDARD ELEKTRIK LORENZ) 12 September 1990 see column 2, line 8 - column 4, line 16 see column 4, line 42 - column 5, line 6 see column 5, line 15 - column 7, line 36 --- -/--	1-6, 12-15

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

21 September 1994

Date of mailing of the international search report

19. 10. 94

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+ 31-70) 340-3016

Authorized officer

Van den Berg, J.G.J.

INTERNATIONAL SEARCH REPORT

International application No.
PCT/GB 94/01713

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	JOURNAL OF LIGHTWAVE TECHNOLOGY, vol.11, no.1, 1 January 1993, NEW YORK US pages 60 - 68, XP377986 ROBERT OLSHANSKY ET AL. 'Subcarrier multiplexed broadband service network: A flexible platform for broadband subscriber services.'	1,7-9
Y	see page 60, column 2, line 32 - page 61, column 1, line 12 see page 62, column 1, line 14 - line 30 see page 66, column 1, line 21 - page 67, column 2, line 21	10
Y	--- JOURNAL OF LIGHTWAVE TECHNOLOGY, vol.11, no.1, 1 January 1993, NEW YORK US pages 106 - 115, XP377990 TOSHIYUKI TSUCHYA ET AL. 'Analysis and design for optical video transport/distribution system with video on demand service.' see page 108, column 1, line 13 - line 17; figure 1 see page 109, column 2, line 22 - page 110, column 1, line 32	10
A	--- WO,A,91 09478 (BRITISH TELECOMMUNICATIONS PUBLIC LIMITED COMPANY) 27 June 1991 see page 2, line 4 - line 13 see page 2, line 22 - page 3, line 18 see page 4, line 3 - page 5, line 26	7,8
A	--- REVUE HF, vol.XIV, no.7/8, 1990, OPHAIN BE pages 194 - 210, XP208851 D. MESTDAGH ET AL. 'Broadband passive optical access networks' see page 196, line 40 - line 49 see page 198, line 21 - line 48 see page 200, line 29 - line 46 see page 206, line 1 - line 17 -----	1-15

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.
PCT/GB 94/01713

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
EP-A-0380945	08-08-90	DE-A-	3902746	09-08-90
		AU-B-	624208	04-06-92
		AU-A-	4724589	09-08-90
		JP-A-	2238739	21-09-90
		US-A-	5058102	15-10-91

EP-A-0386466	12-09-90	DE-A-	3907497	13-09-90
		AU-B-	623498	14-05-92
		AU-A-	5018090	13-09-90

WO-A-9109478	27-06-91	AU-B-	639739	05-08-93
		AU-A-	6913691	18-07-91
		EP-A-	0504248	23-09-92
		JP-T-	5504874	22-07-93

THIS PAGE BLANK (USPTO)




Fig.1.




Fig.2.




Fig. 3.

THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

This Page Blank (uspto)